

VETROSPACE™

GROUPSPACE

S



The S is the smallest member of the Groupspace family. Groupspace S can fit almost anywhere as it has the smallest footprint of all the Groupspaces, but comes with all the benefits. Perfect for face-to-face meetings, phone calls, video conferences, or as a private little office.

Technical information

Dimensions (Ext) W210 / D110 / H240cm

Dimensions (Int) W200 / D100 / H220cm

Weight 760Kg

Installation height requirement >250cm

Sound Reduction STI: 0.03 Ds: 30.6dB (ISO 23351-1)

Glass 16,7mm sound control safety glass

Exterior surface White or Black laminate, optional finishes* or ECOfelt acoustic felt*.

Door Dual panel sliding door. Side can be chosen. Unimpeded access.

Structure Modular, 5 options.

Connectivity 230V/16A

Power 75W (Average)

Power 300W (Maximum)

Energy consumption 1.8kWh/24h

Sockets 4 pcs Fault current protected.

Optional extras USB ports (1.5A)+ RJ45, HDMI, automatic fire extinguishing system, electric dimming glass, electrical locking, automatic doors, furniture sets.

STI value Classification

< 0,05	Exceptional
0,05-0,20	Good
0,20-0,40	Satisfactory

Frame



RAL 9004
Black



RAL 9016
White



Other
RAL
color*

Carpet



Light Grey
506



Dark Grey
902

ECOfelt



Light Grey
953



Natural
White
955



Dark Grey
923



Other
ECOfelt
color*

Structure



* Extra cost

CUBE Technical information

Interior surface ECOfelt wool

Floor Recycled Econyl SD

Ventilation Smart, +40l/s

Lighting LED, microlens 4000K



CLEAN Technical information


Interior surface ECOfelt wool

Floor Recycled Econyl SD

Ventilation Smart, HEPA 13, +40l/s

Lighting VLD antibacterial lighting

Treatment Antimicrobial nano coating



HEALTH Technical information

Interior ceiling ECOfelt wool

Interior walls Laminate (HPL)

Flooring Mipolam Robus EL7 ESD

Ventilation Smart, HEPA 13 (in and out), +40l/s

Lighting VLD antibacterial lighting

Treatment Antimicrobial nano coating

